

Ultrahigh Purity, DP Series, Shutoff



Part No.

6LVV-DPVFR4-P-C

Part Description

316L VIM-VAR UHP Diaphragm Sealed Valve, Polyimide Seat, 1/4 in. Female VCR Fitting, SC-01 Cleaned, NC Actuator

Specifications

General	
Body Material	316L VIM-VAR
Cleaning Process	Ultrahigh-Purity Process Specification (SC-01)
Connection 1 Size	1/4 in.
Connection 1 Type	Face Seal (Metal Gasket) Female VCR
Connection 2 Size	1/4 in.
Connection 2 Type	Face Seal (Metal Gasket) Female VCR
eClass (4.1)	37010206
eClass (5.1.4)	37011800
eClass (6.0)	37011801
eClass (6.1)	37011801
UNSPSC (10.0)	40141621
UNSPSC (11.0501)	40141621
UNSPSC (13.0601)	40141621
UNSPSC (15.1)	40141621
UNSPSC (4.03)	40141600
UNSPSC (AirLiquide)	G2204-99
UNSPSC (PGE)	401416AL
UNSPSC (SWG01)	40141600

! The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

⚠ Warning: Do not mix/interchange Swagelok products or components not governed by industrial design standards, including Swagelok tube fitting end connections, with those of other manufacturers.